

# Preliminary "High Frequency Ceramic Solutions"

**2 GHz Antenna** Small form factor

Detail Specification: 03/04/09

**P/N 2000AT18A0075**

Page 1 of 3

## General Specifications

Part Number	2000AT18A0075
Frequency Range	1965 - 2040 Mhz
Peak Gain	0.3 dBi typ. (XZ-V)
Average Gain	-3 dBi typ. (XZ-V)
Return Loss	9.5 dB min.

<b>Input Power</b>	2 Watts max.
<b>VSWR</b>	2 max
<b>Operating Temperature</b>	-40 to +85°C
<b>Reel Quantity</b>	3000

No.	Function	Terminal Configuration
1	Feeding Point	
2	NC	


## Mechanical Dimensions

	In	mm	
L	0.126 ± 0.008	3.20 ± 0.20	
W	0.063 ± 0.008	1.60 ± 0.20	
T	0.051 ± 0.008	1.30 ± 0.20	
a	0.020 ± 0.012	0.50 ± 0.30	

## Mounting Considerations

Mount these devices with brown mark facing up. Units: mm

\*Line width should be designed to provide 50Ω impedance matching characteristics.



Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.

Preliminary "High Frequency Ceramic Solutions"

**2 GHz Antenna**


**P/N 2000AT18A0075**

Detail Specification: 03/04/09


Page 2 of 3

**Typical Electrical Characteristics (T=25°C)**

**Test Board:**



**Return Loss with matching circuit**



Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.

**JOHANSON**  
**TECHNOLOGY**

[www.johansontechnology.com](http://www.johansontechnology.com)

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2009 Johanson Technology, Inc. All Rights Reserved


# Preliminary "High Frequency Ceramic Solutions"

## 2 GHz Antenna

Detail Specification: 03/04/09

P/N 2000AT18A0075

Page 2 of 3



Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.