

**Johanson Company: Johanson Technology inc.** Product Release Date: 21 April, 2016

Deprecated P/N: 1720BL15B0200-EB1SMA

Datasheet Date: 03-29-2024

Description: RF Baluns, Eval Board, 805,  
625-2815MHz, 2W, 1.5dB, Ni/Sn (RoHS), 1:4  
Wideband Balun, Non-Conductive Bags

Life Cycle Stage: Active - Production

Schedule B: 8534

ECCN: EAR99

RoHS Compliance: Yes, RoHS 10/10

REACH: 1

Country of Origin: TW

Product Family: Integrated Passive Components

Product Subfamily: RF Baluns

Marking: Special

Web Page Link:

<https://johansontechnology.com/baluns>

Thickness (Max): 0.041

Thickness (Min): 0.033

End Band (Min):

End Band (Max):

Standard Item: 1

Lead Time Typical (Weeks)\*:

\*This can vary significantly so it is important  
to obtain a quotation with lead time for  
production planning purposes. 14

Length (Min): 0.075

Length (Max): 0.083

Width (Min): 0.045

Width (Max): 0.053

Packaging: Non-Conductive Bags

Packaging Qty: 1

Operating Temp Range: -40°C to +85°C

Storage Temp Range (Packaged): -65°C to  
+125°C

Storage Temp Range (Non Operating): +5°C to  
+40°C with RH 20% to 70%