

Johanson Company: Johanson Technology inc. Product Release Date: 14 October, 2015

Deprecated P/N: 2450BL05A0100-EB1SMA

Web Page Link:

<https://johansontechnology.com/baluns>

Datasheet Date: 04-25-2024

Thickness (Max): 0.018

Description: RF Baluns, Eval Board, 201,
2300-2690MHz, 2W, 0.55000000000000004dB,
Ag/Pt (RoHS), Micro Balun for
BLE/WiFi/LTE/Cellular, Non-Conductive Bags

End Band (Min):

End Band (Max):

Life Cycle Stage: Active - Production

Standard Item: 1

Schedule B: 8534

Lead Time Typical (Weeks)*:

*This can vary significantly so it is important
to obtain a quotation with lead time for
production planning purposes. 20

ECCN: EAR99

RoHS Compliance: Yes, RoHS 10/10

Length (Min): 0.024

REACH: 1

Length (Max): 0.028

Country of Origin: TW

Width (Min): 0.018

Product Family: Integrated Passive Components

Width (Max): 0.022

Product Subfamily: RF Baluns

Packaging: Non-Conductive Bags

Marking: Special

Packaging Qty: 1

Operating Temp Range: -40°C to +85°C

Storage Temp Range (Packaged): -65°C to
+125°CStorage Temp Range (Non Operating): +5°C to
+40°C with RH 20% to 70%