

Johanson Company: Johanson Technology inc. Product Release Date: 10 January, 2006

Deprecated P/N: 2450BL15B100-EB2SMA

Web Page Link:

<https://johansontechnology.com/baluns>

Datasheet Date: 05-01-2024

Thickness (Max): 0.037

Description: RF Baluns, Eval Board, 805,
2400-2500MHz, 3W, 1dB, Ni/Sn (RoHS), 1:2 Balun,
Non-Conductive Bags

Thickness (Min): 0.029

Life Cycle Stage: Active - Production

End Band (Min):

End Band (Max):

Schedule B: 8534

Standard Item: 1

ECCN: EAR99

Lead Time Typical (Weeks)*:

*This can vary significantly so it is important
to obtain a quotation with lead time for
production planning purposes. 20

RoHS Compliance: Yes, RoHS 10/10

REACH: 1

Length (Min): 0.075

Country of Origin: TW

Length (Max): 0.083

Product Family: Integrated Passive Components

Width (Min): 0.045

Product Subfamily: RF Baluns

Width (Max): 0.053

Marking: Special

Packaging: Non-Conductive Bags

Packaging Qty: 1

Operating Temp Range: -40°C to +85°C

Storage Temp Range (Packaged): -65°C to
+125°CStorage Temp Range (Non Operating): +5°C to
+40°C with RH 20% to 70%