

Johanson Company: Johanson Technology inc. Product Release Date: 05 November, 2020

Deprecated P/N: 4550BL14A0100T

Thickness (Max): 0.028

Datasheet Date: 04-16-2024

Thickness (Min): 0.020

Description: RF Baluns, 603, 3200-6000MHz, 1W,
1.2/1.4, Ni/Sn (RoHS), 3.2 - 6.0 GHz Wideband
Ceramic Balun, 1:2 Impedance Ratio, EIA 0603, 7"
Reel Paper Tape

End Band (Min):

End Band (Max):

Life Cycle Stage: Active - Production

Lead Time Typical (Weeks)*:

*This can vary significantly so it is important
to obtain a quotation with lead time for
production planning purposes. 20

Schedule B: 8534

Length (Min): 0.059

ECCN: EAR99

Length (Max): 0.067

RoHS Compliance: Yes, RoHS 10/10

Width (Min): 0.027

REACH: 1

Width (Max): 0.035

Country of Origin: TW

Packaging: 7" Reel Paper Tape

Product Family: Integrated Passive Components

Packaging Qty: 4000

Product Subfamily: RF Baluns

Operating Temp Range: -40°C to +105°C

Marking: Special

Storage Temp Range (Packaged): -40°C to
+105°CStorage Temp Range (Non Operating): +5°C to
+35°C with RH 45% to 75%