

**Johanson Company: Johanson Technology inc.** Product Release Date: 30 November, -0001

Deprecated P/N: 5425BL07C0100S

Thickness (Max): 0.017

Datasheet Date: 03-29-2024

Thickness (Min): 0.013

Description: RF Baluns, 402, 4900-5950MHz, 2  
Watts maW, 0.55, Ni/Sn (RoHS), 5.4GHz Ultra Mini  
Balun, Bulk

End Band (Min):

End Band (Max):

Life Cycle Stage: Under development - Can be  
forecasted (no orders accepted)

Lead Time Typical (Weeks)\*:

\*This can vary significantly so it is important  
to obtain a quotation with lead time for  
production planning purposes. 14

Schedule B: 8534

Length (Min): 0.037

ECCN: EAR99

Length (Max): 0.041

RoHS Compliance: Yes, RoHS 10/10

Width (Min): 0.016

Country of Origin: TW

Width (Max): 0.024

Product Family: Integrated Passive Components

Packaged Weight (lb) Arm: 0.00

Product Subfamily: RF Baluns

Packaging: Bulk

Capacitance Value: 0.000

Operating Temp Range: -40°C to +85°C

Voltage: 0.0

Storage Temp Range (Packaged): -65°C to  
+125°C

Marking: Special

Storage Temp Range (Non Operating): +5°C to  
+40°C with RH 20% to 70%