Johanson Part Number QSCP251Q100G1GV001T

Legacy P/N: 251R14S100GV4T Description: Capacitors High-Q MLC S-Series, 0603, Hi-Q NP0/C0G, 250V, 10pF±2%, Ni/Sn (RoHS), 7" Reel Paper Tape Life Cycle Stage: Active NCNR: No AEC Q200 Qualified: No Thickness (Max): 0.035 Schedule B: 8532.24.00.20 Thickness (Min): 0.027 ITAR: No End Band (max): 0.020 ROHS Compliance: Yes, RoHS 10/10 Standard Item: Yes REACH: Yes Lead Time Typical (Weeks)*: 8 Country of Origin: US Length (Min): 0.056 Product Family: Capacitors High-Q MLC S-Series Width (Max): 0.038 Cap Unit of Meas: pF Tolerance: ±2% Packaged Width (Ib) Arm: 0.35 Voltage: 250.0 Packaging Qty: 4000 Dielectric Temp Coefficient: Hi-Q NP0/C0G Product Release Date: Jan. 3, 2006, 8 a.m. Specifications (EIA): 0603 Specifications (EIA): 0603 Specifications (EIA): 0603 Specification Number: 35S0118E Specification Number: 35S0118 Specification Page (Idea Specification Pa	Johanson Part Number: QSCP251Q100G1GV001T	Johanson Company: JTI
Hi-Q NPO/COG, 250V, 10pF±2%, Ni/Sn (RoHS), 7" Reel Paper Tape Life Cycle Stage: Active NCNR: No AEC Q200 Qualified: No Thickness (Max): 0.035 Schedule B: 8532.24.00.20 Thickness (Min): 0.027 ITAR: No End Band (Min): 0.01 ECCN: EAR99 End Band (max): 0.020 RoHS Compliance: Yes, RoHS 10/10 Standard Item: Yes Lead Time Typical (Weeks)*: 8 Country of Origin: US Length (Min): 0.056 Product Family: Capacitors Product Subfamily: Capacitors High-Q MLC S-Series Width (Min): 0.026 Capacitance Value: 10.000 Width (Max): 0.038 Cap Unit of Meas: pF Part Weight (mg): 4.50 Tolerance: ±2% Packaged Width (Ib) Arm: 0.35 Voltage: 250.0 Packaging: 7" Reel Paper Tape Dielectric Temp Coefficient: Hi-Q NPO/COG Packaging Qty: 4000 Termination: 68 Operating Temp Range: -55°C to +150°C Product Release Date: Ian 3, 2006, 8 a.m. Storage Temp Range (None Operating): +5°C to	Legacy P/N: 251R14S100GV4T	Size for Capacitors (EIA): 0603
AEC Q200 Qualified: No Schedule B: 8532.24.00.20 Thickness (Min): 0.027 ITAR: No End Band(Min): 0.01 ECCN: EAR99 End Band (max): 0.020 RoHS Compliance: Yes, RoHS 10/10 Standard Item: Yes REACH: Yes Lead Time Typical (Weeks)*: 8 Country of Origin: US Length (Min): 0.056 Product Family: Capacitors Length (Max): 0.068 Product Subfamily: Capacitors High-Q MLC S-Series Width (Min): 0.026 Capacitance Value: 10.000 Width (Max): 0.038 Cap Unit of Meas: pF Part Weight (mg): 4.50 Tolerance: ±2% Packaged Width (lb) Arm: 0.35 Voltage: 250.0 Packaging: 7" Reel Paper Tape Dielectric Temp Coefficient: Hi-Q NP0/COG Packaging Qty: 4000 Termination: 68 Operating Temp Range: -55°C to +150°C Marking: No Mark Storage Temp Range (Packaged): -65°C to +150°C Product Balases Date: Ian 3, 2006, 8 a.m. Storage Temp Range (None Operating): +5°C to	Hi-Q NP0/C0G, 250V, 10pF±2%, Ni/Sn (RoHS), 7"	Specification Number: 35S0118E
Schedule B: 8532.24.00.20 Thickness (Min): 0.027 ITAR: No End Band(Min): 0.01 ECCN: EAR99 End Band (max): 0.020 RoHS Compliance: Yes, RoHS 10/10 Standard Item: Yes REACH: Yes Lead Time Typical (Weeks)*: 8 Country of Origin: US Length (Min): 0.056 Product Family: Capacitors Length (Max): 0.068 Product Subfamily: Capacitors High-Q MLC S-Series Width (Min): 0.026 Capacitance Value: 10.000 Width (Max): 0.038 Cap Unit of Meas: pF Part Weight (mg): 4.50 Tolerance: ±2% Packaged Width (Ib) Arm: 0.35 Voltage: 250.0 Packaging: 7" Reel Paper Tape Dielectric Temp Coefficient: Hi-Q NP0/C0G Packaging Oty: 4000 Termination: 68 Operating Temp Range: -55°C to +150°C Marking: No Mark Storage Temp Range (Packaged): -65°C to +150°C Storage Temp Range (None Operating): +5°C to	Life Cycle Stage: Active	NCNR: No
ITAR: No End Band (Min): 0.01 ECCN: EAR99 End Band (max): 0.020 RoHS Compliance: Yes, RoHS 10/10 Standard Item: Yes REACH: Yes Lead Time Typical (Weeks)*: 8 Country of Origin: US Length (Min): 0.056 Product Family: Capacitors Length (Max): 0.068 Product Subfamily: Capacitors High-Q MLC S-Series Width (Min): 0.026 Capacitance Value: 10.000 Width (Max): 0.038 Cap Unit of Meas: pF Part Weight (mg): 4.50 Tolerance: ±2% Packaged Width (Ib) Arm: 0.35 Voltage: 250.0 Packaging: 7" Reel Paper Tape Dielectric Temp Coefficient: Hi-Q NP0/C0G Packaging Qty: 4000 Termination: 68 Operating Temp Range: -55°C to +150°C Marking: No Mark Storage Temp Range (None Operating): +5°C to	AEC Q200 Qualified: No	Thickness (Max): 0.035
ECCN: EAR99 End Band (max): 0.020 RoHS Compliance: Yes, RoHS 10/10 Standard Item: Yes REACH: Yes Lead Time Typical (Weeks)*: 8 Country of Origin: US Length (Min): 0.056 Product Family: Capacitors Product Subfamily: Capacitors High-Q MLC S-Series Width (Min): 0.026 Capacitance Value: 10.000 Width (Max): 0.038 Cap Unit of Meas: pF Part Weight (mg): 4.50 Tolerance: ±2% Packaged Width (lb) Arm: 0.35 Voltage: 250.0 Packaging: 7" Reel Paper Tape Dielectric Temp Coefficient: Hi-Q NP0/COG Packaging Qty: 4000 Termination: 68 Operating Temp Range: -55°C to +150°C Marking: No Mark Storage Temp Range (None Operating): +5°C to	Schedule B: 8532.24.00.20	Thickness (Min): 0.027
RoHS Compliance: Yes, RoHS 10/10 REACH: Yes Lead Time Typical (Weeks)*: 8 Country of Origin: US Length (Min): 0.056 Product Family: Capacitors Length (Max): 0.068 Product Subfamily: Capacitors High-Q MLC S-Series Width (Min): 0.026 Capacitance Value: 10.000 Width (Max): 0.038 Cap Unit of Meas: pF Part Weight (mg): 4.50 Tolerance: ±2% Packaged Width (Ib) Arm: 0.35 Voltage: 250.0 Packaging: 7" Reel Paper Tape Dielectric Temp Coefficient: Hi-Q NP0/C0G Packaging Qty: 4000 Termination: 68 Operating Temp Range: -55 °C to +150 °C Marking: No Mark Storage Temp Range (Packaged): -65 °C to +150 °C Product Release Date: Iap 3, 2006, 8 a.m. Storage Temp Range (None Operating): +5 °C to	ITAR: No	End Band(Min): 0.01
REACH: Yes Country of Origin: US Length (Min): 0.056 Product Family: Capacitors Length (Max): 0.068 Product Subfamily: Capacitors High-Q MLC S-Series Width (Min): 0.026 Capacitance Value: 10.000 Width (Max): 0.038 Cap Unit of Meas: pF Part Weight (mg): 4.50 Tolerance: ±2% Packaged Width (Ib) Arm: 0.35 Voltage: 250.0 Packaging: 7" Reel Paper Tape Dielectric Temp Coefficient: Hi-Q NP0/C0G Packaging Qty: 4000 Termination: 68 Operating Temp Range: -55°C to +150°C Marking: No Mark Storage Temp Range (None Operating): +5°C to	ECCN: EAR99	End Band (max): 0.020
Country of Origin: US Length (Min): 0.056 Product Family: Capacitors Length (Max): 0.068 Product Subfamily: Capacitors High-Q MLC S-Series Width (Min): 0.026 Capacitance Value: 10.000 Width (Max): 0.038 Cap Unit of Meas: pF Part Weight (mg): 4.50 Tolerance: ±2% Packaged Width (lb) Arm: 0.35 Voltage: 250.0 Packaging: 7" Reel Paper Tape Dielectric Temp Coefficient: Hi-Q NP0/C0G Packaging Qty: 4000 Termination: 68 Operating Temp Range: -55°C to +150°C Marking: No Mark Storage Temp Range (Packaged): -65°C to +150°C Storage Temp Range (None Operating): +5°C to	RoHS Compliance: Yes, RoHS 10/10	Standard Item: Yes
Product Family: Capacitors Length (Max): 0.068 Product Subfamily: Capacitors High-Q MLC S-Series Width (Min):0.026 Capacitance Value: 10.000 Width (Max): 0.038 Cap Unit of Meas: pF Part Weight (mg): 4.50 Tolerance: ±2% Packaged Width (lb) Arm: 0.35 Voltage: 250.0 Packaging: 7" Reel Paper Tape Dielectric Temp Coefficient: Hi-Q NP0/C0G Packaging Qty: 4000 Termination: 68 Operating Temp Range: -55 °C to +150 °C Marking: No Mark Storage Temp Range (None Operating): +5 °C to	REACH: Yes	Lead Time Typical (Weeks)*: 8
Product Subfamily: Capacitors High-Q MLC S-Series Width (Min):0.026 Capacitance Value: 10.000 Width (Max): 0.038 Cap Unit of Meas: pF Part Weight (mg): 4.50 Tolerance: ±2% Packaged Width (lb) Arm: 0.35 Voltage: 250.0 Packaging: 7" Reel Paper Tape Dielectric Temp Coefficient: Hi-Q NP0/C0G Packaging Qty: 4000 Termination: 68 Operating Temp Range: -55°C to +150°C Marking: No Mark Storage Temp Range (Packaged): -65°C to +150°C Storage Temp Range (None Operating): +5°C to	Country of Origin: US	Length (Min): 0.056
Capacitance Value: 10.000 Width (Max): 0.038 Cap Unit of Meas: pF Part Weight (mg): 4.50 Packaged Width (lb) Arm: 0.35 Voltage: 250.0 Packaging: 7" Reel Paper Tape Dielectric Temp Coefficient: Hi-Q NP0/C0G Packaging Qty: 4000 Termination: 68 Operating Temp Range: -55°C to +150°C Marking: No Mark Storage Temp Range (Packaged): -65°C to +150°C Storage Temp Range (None Operating): +5°C to	Product Family: Capacitors	Length (Max): 0.068
Cap Unit of Meas: pF Part Weight (mg): 4.50 Packaged Width (lb) Arm: 0.35 Voltage: 250.0 Packaging: 7" Reel Paper Tape Dielectric Temp Coefficient: Hi-Q NP0/C0G Packaging Qty: 4000 Termination: 68 Operating Temp Range: -55°C to +150°C Marking: No Mark Storage Temp Range (Packaged): -65°C to +150°C Product Release Date: Jan 3, 2006, 8 a.m. Storage Temp Range (None Operating): +5°C to	Product Subfamily: Capacitors High-Q MLC S-Series	Width (Min):0.026
Tolerance: ±2% Packaged Width (lb) Arm: 0.35 Voltage: 250.0 Packaging: 7" Reel Paper Tape Dielectric Temp Coefficient: Hi-Q NP0/C0G Packaging Qty: 4000 Termination: 68 Operating Temp Range: -55°C to +150°C Marking: No Mark Storage Temp Range (Packaged): -65°C to +150°C Product Release Date: Jan 3, 2006, 8 a.m. Storage Temp Range (None Operating): +5°C to	Capacitance Value: 10.000	Width (Max): 0.038
Voltage: 250.0 Packaging: 7" Reel Paper Tape Dielectric Temp Coefficient: Hi-Q NP0/C0G Packaging Qty: 4000 Termination: 68 Operating Temp Range: -55°C to +150°C Marking: No Mark Storage Temp Range (Packaged): -65°C to +150°C Storage Temp Range (None Operating): +5°C to	Cap Unit of Meas: pF	Part Weight (mg): 4.50
Dielectric Temp Coefficient: Hi-Q NP0/C0G Packaging Qty: 4000 Termination: 68 Operating Temp Range: -55°C to +150°C Marking: No Mark Storage Temp Range (Packaged): -65°C to +150°C Storage Temp Range (None Operating): +5°C to	Tolerance: ±2%	Packaged Width (lb) Arm: 0.35
Termination: 68 Operating Temp Range: -55°C to +150°C Marking: No Mark Storage Temp Range (Packaged): -65°C to +150°C Storage Temp Range (None Operating): +5°C to	Voltage: 250.0	Packaging: 7" Reel Paper Tape
Marking: No Mark Storage Temp Range (Packaged): -65°C to +150°C Storage Temp Range (None Operating): +5°C to	Dielectric Temp Coefficient: Hi-Q NP0/C0G	Packaging Qty: 4000
Product Release Date: Jan 3, 2006, 8 a.m. Storage Temp Range (None Operating): +5°C to	Termination: 68	Operating Temp Range: -55°C to +150°C
	Marking: No Mark	Storage Temp Range (Packaged): -65°C to +150°C
	Product Release Date: Jan. 3, 2006, 8 a.m.	

Harmonization: 8532.24.00.20

Web Page Link: https://www.johansontechnology.com/R14S

Printed from: www.johansontechnology.com/search/pn-detail/QSCP251Q100G1GV001T/

^{*}This can vary significantly so it is important to obtain a quotation with lead time for production planning purposes.