

# Johanson Part Number TDCT500G4R7C1NT001U

|  |   |
|--|---|
| Johanson Part Number: TDCT500G4R7C1NT001U  | Johanson Company: JDI   |
| Legacy P/N: 500R15N4R7CT4U   | Size for Capacitors (EIA): 0805                                       |
| Description: Capacitors SMT, NP0/C0G, 0805, 50V, 4.7pF±0.25pF, Ni/SnPb, 13" Reel Embossed Tape | Specification Number: None  |
| Life Cycle Stage: Active   | NCNR: No  |
| AEC Q200 Qualified: No   | Thickness (Max): 0.050  |
| Schedule B: 8532.24.00.20  | Thickness (Min): None   |
| ITAR: No   | End Band(Min): 0.01   |
| ECCN: EAR99  | End Band (max): 0.030   |
| RoHS Compliance: No  | Standard Item: Yes  |
| REACH: Yes   | Lead Time Typical (Weeks)*: 20  |
| Country of Origin: US, MX, or CN   | Length (Min): 0.070   |
| Product Family: Capacitors   | Length (Max): 0.090   |
| Product Subfamily: Capacitors Surface Mount < 500V   | Width (Min):0.040   |
| Capacitance Value: 4.700   | Width (Max): 0.060  |
| Cap Unit of Meas: pF   | Part Weight (mg): 24.00   |
| Tolerance: ±0.25pF   | Packaged Width (lb) Arm: None   |
| Voltage: 50.0  | Packaging: 13" Reel Embossed Tape                                     |
| Dielectric Temp Coefficient: NP0/C0G   | Packaging Qty: None   |
| Termination: 6   | Operating Temp Range: -55°C to +125°C                                 |
| Marking: No Mark   | Storage Temp Range (Packaged): -65°C to +125°C                        |
| Product Release Date: Jan. 3, 2006, 8 a.m.   | Storage Temp Range (None Operating): +5°C to +40°C with RH 20% to 70% |
| Harmonization: 8532.24.00.20   |   |

\*This can vary significantly so it is important to obtain a quotation with lead time for production planning purposes.

Web Page Link: <https://www.johansondielectrics.com/surface-mount-mlc-capacitors>

Printed from: <https://www.johansontechnology.com/part/TDCT500G4R7C1NT001U/>