

Johanson Part Number TDDD101G2R2C1NT001U

| | |
|---|---|
| Johanson Part Number: TDDD101G2R2C1NT001U | Johanson Company: JDI |
| Legacy P/N: 101R18N2R2CT4U | Size for Capacitors (EIA): 1206 |
| Description: Capacitors SMT, NP0/C0G, 1206, 100V, 2.2pF±0.25pF, Ni/SnPb, 13" Reel Embossed Tape | Specification Number: None |
| Life Cycle Stage: Active | NCNR: No |
| AEC Q200 Qualified: No | Thickness (Max): 0.050 |
| Schedule B: 8532.24.00.20 | Thickness (Min): None |
| ITAR: No | End Band(Min): 0.01 |
| ECCN: EAR99 | End Band (max): 0.030 |
| RoHS Compliance: No | Standard Item: Yes |
| REACH: Yes | Lead Time Typical (Weeks)*: 20 |
| Country of Origin: US, MX, or CN | Length (Min): 0.115 |
| Product Family: Capacitors | Length (Max): 0.135 |
| Product Subfamily: Capacitors Surface Mount < 500V | Width (Min):0.052 |
| Capacitance Value: 2.200 | Width (Max): 0.072 |
| Cap Unit of Meas: pF | Part Weight (mg): 40.00 |
| Tolerance: ±0.25pF | Packaged Width (lb) Arm: None |
| Voltage: 100.0 | Packaging: 13" Reel Embossed Tape |
| Dielectric Temp Coefficient: NP0/C0G | Packaging Qty: None |
| Termination: 6 | Operating Temp Range: -55°C to +125°C |
| Marking: No Mark | Storage Temp Range (Packaged): -65°C to +125°C |
| Product Release Date: Jan. 2, 2006, 8 a.m. | Storage Temp Range (None Operating): +5°C to +40°C with RH 20% to 70% |
| Harmonization: 8532.24.00.20 | |

*This can vary significantly so it is important to obtain a quotation with lead time for production planning purposes.

Web Page Link: <https://www.johansondielectrics.com/surface-mount-mlc-capacitors>

Printed from: <https://www.johansontechnology.com/part/TDDD101G2R2C1NT001U/>