

Johanson Part Number VPDD501W471M1GV001T

| | |
|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| Johanson Part Number: VPDD501W471M1GV001T | Johanson Company: JDI |
| Legacy P/N: 501R18W471MV4T | Size for Capacitors (EIA): 1206 |
| Description: Capacitors HVS PME, 1206, X7R, 500V, 470pF±20%, Ni/Sn (RoHS), 7" Reel Paper Tape | Specification Number: None |
| Life Cycle Stage: Active | NCNR: No |
| AEC Q200 Qualified: No | Thickness (Max): 0.067 |
| Schedule B: 8532.24.00.20 | Thickness (Min): None |
| ITAR: No | End Band(Min): 0.01 |
| ECCN: EAR99 | End Band (max): 0.030 |
| RoHS Compliance: Yes, RoHS 10/10 | Standard Item: Yes |
| REACH: Yes | Lead Time Typical (Weeks)*: 16 |
| Country of Origin: US, MX, TW, or CN | Length (Min): 0.115 |
| Product Family: Capacitors | Length (Max): 0.135 |
| Product Subfamily: Capacitors High Voltage SMD ≥ 500V | Width (Min):0.052 |
| Capacitance Value: 470.000 | Width (Max): 0.072 |
| Cap Unit of Meas: pF | Part Weight (mg): None |
| Tolerance: ±20% | Packaged Width (lb) Arm: None |
| Voltage: 500.0 | Packaging: 7" Reel Paper Tape |
| Dielectric Temp Coefficient: X7R | Packaging Qty: 3000 |
| Termination: 68 | Operating Temp Range: -55°C to +125°C |
| Marking: No Mark | Storage Temp Range (Packaged): -65°C to +125°C |
| Product Release Date: Jan. 2, 2006, 8 a.m. | Storage Temp Range (None Operating): +5°C to +40°C with RH 20% to 70% |
| Harmonization: 8532.24.00.20 | |

*This can vary significantly so it is important to obtain a quotation with lead time for production planning purposes.

Web Page Link: <https://www.johansondielectrics.com/high-voltage-mlc-capacitors>

Printed from: <https://www.johansontechnology.com/part/VPDD501W471M1GV001T/>