

# Johanson Part Number VPEH302G680J2GV002B

|  |   |
|--|---|
| Johanson Part Number: VPEH302G680J2GV002B  | Johanson Company: JDI   |
| Legacy P/N: 302S48N680JV6+AQ   | Size for Capacitors (EIA): 2225                                       |
| Description: Capacitors HVS PME, 2225, NP0/C0G, 3000V, 68pF±5%, Ni/Sn (RoHS), Bulk, AEC Q200 | Specification Number: None  |
| Life Cycle Stage: Active   | NCNR: No  |
| AEC Q200 Qualified: Yes  | Thickness (Max): 0.160  |
| Schedule B: 8532.24.00.20  | Thickness (Min): None   |
| ITAR: No   | End Band(Min): 0.01   |
| ECCN: EAR99  | End Band (max): 0.040   |
| RoHS Compliance: Yes, RoHS 10/10   | Standard Item: Yes  |
| REACH: Yes   | Lead Time Typical (Weeks)*: 18  |
| Country of Origin: US, MX, TW, or CN   | Length (Min): 0.215   |
| Product Family: Capacitors   | Length (Max): 0.235   |
| Product Subfamily: Capacitors High Voltage SMD ≥ 500V  | Width (Min):0.240   |
| Capacitance Value: 68.000  | Width (Max): 0.270  |
| Cap Unit of Meas: pF   | Part Weight (mg): 590.00  |
| Tolerance: ±5%   | Packaged Width (lb) Arm: None   |
| Voltage: 3000.0  | Packaging: Bulk   |
| Dielectric Temp Coefficient: NP0/C0G   | Packaging Qty: None   |
| Termination: 68  | Operating Temp Range: -55°C to +125°C                                 |
| Marking: EIA Mark  | Storage Temp Range (Packaged): -65°C to +125°C                        |
| Product Release Date: Jan. 9, 2006, 8 a.m.   | Storage Temp Range (None Operating): +5°C to +40°C with RH 20% to 70% |
| Harmonization: 8532.24.00.20   |   |

\*This can vary significantly so it is important to obtain a quotation with lead time for production planning purposes.

Web Page Link: <https://www.johansondielectrics.com/high-voltage-mlc-capacitors>

Printed from: <https://www.johansontechnology.com/part/VPEH302G680J2GV002B/>